

according to Regulation (EC) No 1907/2006

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 21.03.2019

Product code: 950203

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Further trade names

possible alloys: Sn60Pb40; Sn63Pb37; Sn64Pb36; Sn60Pb38Cu2; Sn60Pb38Ag2; Sn60Pb36Ag4; Sn62Pb36Ag2; Pb60Sn40; Pb90Sn10; Pb62Sn27Ag3; Pb93Sn5Ag2; Pb95,5Sn3Ag1,5

2220; 3135; B2012; 26Q; 32Q; B211; Cobar 393

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Solder wire

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	Balver Zinn Josef Jost GmbH & Co. KG	
Street:	Blintroper Weg 11	
Place:	D-58802 Balve	
Telephone:	+49 2375 915-0	Telefax:+49 2375 915-1700
Responsible Department:	sds@balverzinn.com	
1.4. Emergency telephone	Chemtrec: +44(0) 870-8200418	

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Reproductive toxicity: Repr. 1A Reproductive toxicity: Lact. Specific target organ toxicity - repeated exposure: STOT RE 1 Hazard Statements: May damage fertility. May damage the unborn child. May cause harm to breast-fed children. Causes damage to organs through prolonged or repeated exposure.

2.2. Label elements

Additional advice on labelling

Labelling according to Regulation (EC) No. 1272/2008 [CLP]: none For this product, a hazard label is not required according to section 1.3.4 of the CLP regulation.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. No risks worthy of mention. Please observe the information on the safety data sheet at all times.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization Solder wire

Hazardous components

CAS No	Chemical name	Quantity
--------	---------------	----------



Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date	e: 21.03.2019	Product code	950203	Page 2 of 11
	EC No	Index No	REACH No	
	GHS Classification	ł	·	
7439-92-1	lead massive [particle diam	eter >= 1 mm]		95 - <= 100 %
	231-100-4	082-014-00-7	01-2119513221-59	
	Repr. 1A, Lact., STOT RE 1	; H360FD H362 H372		
7440-31-5	tin			2 - 65 %
	231-141-8		01-2119486474-28	
			•	
7440-22-4	silver			0,2 - 5 %
	231-131-3		01-2119555669-21	
7440-50-8	copper			0 - 5 %
	231-159-6			
65997-06-0	Rosin, hydrogenated			1 - < 5 %
	266-041-3			

Full text of H and EUH statements: see section 16.

Further Information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: lead massive [particle diameter >= 1 mm] CAS n°: 7439-92-1

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

No special measures are necessary.

The melted product can cause severe burns. After contact with molten product, cool skin area rapidly with cold water. Burns caused by molten material must be treated clinically.

After contact with eyes

No special measures are necessary.

After ingestion

No special measures are necessary.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Sand

Suitable extinguishing media

according to Regulation (EC) No 1907/2006

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 21.03.2019

Product code: 950203

Page 3 of 11

Extinguishing powder D -powder

Unsuitable extinguishing media

Extinguishing media which must not be used for safety reasons: Water

High power water jet Water spray jet

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Metal oxide smoke, toxic

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

6.2. Environmental precautions

No special measures are necessary.

6.3. Methods and material for containment and cleaning up

Take up mechanically, placing in appropriate containers for disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Process within closed systems. Do not breathe smoke. Do not breathe dust.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

No special measures are necessary.

Hints on joint storage

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances. Infectious substances.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection



according to Regulation (EC) No 1907/2006

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 21.03.2019

Product code: 950203

Page 4 of 11

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7440-50-8	Copper, dusts and mists (as Cu)	-	1		TWA (8 h)	WEL
		-	2		STEL (15 min)	WEL
7440-50-8	Copper, fume	-	0.2		TWA (8 h)	WEL
-	Lead other than lead alkyls		0.15		TWA (8 h)	CLAW
7440-22-4	Silver, metallic	-	0.1		TWA (8 h)	WEL
-	Tin compounds, inorganic, except SnH4, (as Sn)	-	2		TWA (8 h)	WEL
		-	4		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
7439-92-1	Lead (woman of reproductive capacity)	lead	20 µg/dl	blood	Random

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
7440-31-5	tin		•	
Consumer DN	NEL, long-term	inhalation	systemic	3,476 mg/m ³
Consumer DN	NEL, acute	inhalation	systemic	3,476 mg/m ³
Worker DNEL	., long-term	inhalation	systemic	11,75 mg/m ³
Worker DNEL	., acute	inhalation	systemic	11,75 mg/m ³
Consumer DN	IEL, long-term	dermal	systemic	80 mg/kg bw/day
Worker DNEL	., acute	dermal	systemic	133,3 mg/kg bw/day
Consumer DN	NEL, acute	dermal	systemic	80 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	133,3 mg/kg bw/day
Consumer DN	NEL, acute	oral	systemic	80 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	80 mg/kg bw/day
7440-22-4	silver			
Consumer DN	IEL, long-term	oral	systemic	1,2 mg/kg bw/day
Worker DNEL	., long-term	inhalation	systemic	0,1 mg/m ³
Consumer DN	IEL, long-term	inhalation	systemic	0,04 mg/m ³
7440-50-8	copper			
Worker DNEL	., acute	dermal	systemic	273 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	273 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	20 mg/m ³
Worker DNEL	, long-term	inhalation	local	1 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	137 mg/kg bw/day



Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision da	ate: 21.03.2019	Product code: 950203		Page 5 of 11
Worker DN	EL, long-term	dermal	systemic	137 mg/kg bw/day
Worker DNE	EL, acute	inhalation	systemic	20 mg/m ³
Consumer [Consumer DNEL, long-term		local	1 mg/m³
PNEC valu	les			
CAS No	Substance			

CAS No	Substance	
Environmental compartment		Value
7440-22-4	silver	
Soil		1,41 mg/kg
Freshwater		0,00004 mg/l
Marine sedim	nent	438,13 mg/kg
Freshwater s	ediment	438,13 mg/kg
Marine water		0,00086 mg/l
Micro-organisms in sewage treatment plants (STP)		0,025 mg/l
7440-50-8	copper	
Freshwater		0,0078 mg/l
Marine water		0,0052 mg/l
Freshwater s	ediment	87 mg/kg
Marine sediment		678 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,23 mg/l
Soil		65 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. Process within closed systems.

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. Use protective skin cream before handling the product.

Eye/face protection

Wear eye/face protection.

Hand protection

Wear suitable gloves.

for coarse soldering works: heat insulating.

Skin protection

Protective clothing (heat-resistant)

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Insufficient ventilation.

exceeding exposure limit values

Suitable respiratory protective equipment: Particle filter device (DIN EN 143) Type: P3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.



according to Regulation (EC) No 1907/2006

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 21.03.2019

Product code: 950203

Page 6 of 11

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

No special environmental measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid	
Colour:	metallic, silver	
Odour:	odourless	
pH-Value:		not applicable
Changes in the physical state		
Melting point:		not determined
Initial boiling point and boiling range:		not determined
Sublimation point:		not determined
Softening point:		not determined
Flash point:		not determined
Flammability		
Solid:		not determined
Explosive properties none		
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Ignition temperature:		not determined
Auto-ignition temperature Solid:		not determined
Decomposition temperature:		not determined
Oxidizing properties none		
Vapour pressure:		not determined
Density:		not determined
Bulk density:		not determined
Water solubility:		insoluble
Solubility in other solvents insoluble		
Viscosity / dynamic:		not determined
Viscosity / kinematic:		not determined
9.2. Other information		
Solid content:		not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.



according to Regulation (EC) No 1907/2006

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision of	date: 21	.03.2019
-------------	----------	----------

Product code: 950203

Page 7 of 11

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Can be released in case of fire: Metal oxide smoke, toxic

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
7439-92-1	lead massive [particle dia	ameter >= 1	mm]				
	oral	LD50 mg/kg	> 2000	Rat	Study report (2003)	OECD Guideline 423	
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2003)	OECD Guideline 402	
7440-31-5	tin						
	oral	LD50 mg/kg	>2000	Rat	ECHA Dossier		
	dermal	LD50 mg/kg	>2000	Rat	ECHA Dossier		
	inhalation (4 h) aerosol	LC50 mg/l	(>4,75)	Rat	ECHA Dossier		
7440-22-4	silver						
	oral	LD50 mg/kg	>2000	Rat	ECHA Dossier		
	dermal	LD50 mg/kg	>2000	Rat	ECHA Dossier		
	inhalation (4 h) aerosol	LC50 mg/l	>5,16	Rat	ECHA Dossier		
7440-50-8	copper						
	inhalation (4 h) aerosol	LC50 mg/l	>5,11	Rat	ECHA Dossier		

Irritation and corrosivity

Based on available data, the classification criteria are not met. Skin corrosion/irritation: Not an irritant. Serious eye damage/eye irritation: Not an irritant.

Sensitising effects

Based on available data, the classification criteria are not met. Respiratory or skin sensitisation: not sensitising.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 21.03.2019	Product code: 950203	Page 8 of 11

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

BCF

CAS No	Chemical name	BCF	Species	Source
7439-92-1	lead massive [particle diameter >= 1 mm]	40000	Asellus meridianus	Freshwater Biology 7

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

160303 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; inorganic wastes containing hazardous substances; hazardous waste

Waste disposal number of used product

160303 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; inorganic wastes containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 21.03.2019

Product code: 950203

Page 9 of 11

SECTION 14: Transport information

Land transport (ADR/RID)				
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
Inland waterways transport (ADN)				
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
Marine transport (IMDG)				
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
Air transport (ICAO-TI/IATA-DGR)				
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	no			
14.6. Special precautions for user Not restricted				
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Not restricted				
SECTION 15: Regulatory information				

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV): Substances of very high concern, SVHC (REACH, article 59): lead massive [particle diameter >= 1 mm]

Restrictions on use (REACH, annex XVII): Entry 63: lead massive [particle diameter >= 1 mm] Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):

Additional information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. REACH 1907/2006 Appendix XVII, No: 63

National regulatory information

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 21.03.2019	Product code: 950203	Page 10 of 11
Employment restrictions:	Observe restrictions to employment for juvenils according to the work protection guideline' (94/33/EC). Observe employment rest under the Maternity Protection Directive (92/85/EEC) for expecta nursing mothers. Observe employment restrictions for women of child-bearing age.	rictions ant or
Water contaminating class (D): Additional information Observe technical data sheet.	1 - slightly water contaminating	

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

SECTION 16: Other information

Changes

Rev. 1.00; 22.05.2015, Initial release Rev.1.1; 16.11.2016, Indication of changes - chapter: 1, 2, 3, 16. Rev. 2,0; 13.04.2018, Changes in chapter: 2, 3, 15. Rev. 2,1; 03.07.2018, Changes in chapter: 3. Rev. 2.2; 19.02.2019, Indication of changes - chapter: 14, 15, 16. Rev. 2.3; 21.03.2019, Indication of changes - chapter: 8

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route CAS Chemical Abstracts Service DNEL: Derived No Effect Level IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) LOAEL: Lowest observed adverse effect level LOAEC: Lowest observed adverse effect concentration LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level NTP: National Toxicology Program N/A: not applicable OSHA: Occupational Safety and Health Administration PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) SARA: Superfund Amendments and Reauthorization Act SVHC: substance of very high concern TRGS Technische Regeln fuerGefahrstoffe **TSCA:** Toxic Substances Control Act VOC: Volatile Organic Compounds VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse



according to Regulation (EC) No 1907/2006

Leaded Solder Wire Alloy based on Tin-Lead or Lead-Tin with Resin based Flux

Revision date: 21.03.2019

Product code: 950203

Page 11 of 11

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Repr. 1A; H360FD	Calculation method
Lact.; H362	Calculation method
STOT RE 1; H372	Calculation method

Relevant H and EUH statements (number and full text)

H360FD May damage fertility. May damage the unborn child. H362

- May cause harm to breast-fed children.
- H372 Causes damage to organs through prolonged or repeated exposure.

Further Information

Classification according EC regulation 1272/2008 (CLP): - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data. and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)